



# Technical Data Sheet

## Sterling DV Model 8531 4" x 6-5/8" Top Exit Adaptor Installation

*Assembly 95-60924H*

**Publish Date: 6/4/2001**

### **KIT CONTENTS:**

(16)#4500-3435 - Screws 8-32 X 3/8" Type F PH  
( 1)#3160-101 - 5" X 6-1/2" Gasket Ring  
( 1)#3160-102 - 8" X 9-1/2" Gasket Ring  
( 1)#5701-0924H - 4" X 6-5/8" Top Exit Starter Kit

### **TOOLS REQUIRED:**

Phillips Screwdriver

### **PROCEDURE:**

- 1) Remove the 2 phillips head screws on the top of the air plenum on the back of the stove.
- 2) Remove the temporary shipping screws from the inner collar mounting holes.
- 3) Place the 5" X 6 1/2" gasket ring onto the base of the small inner (4") portion of the stove adaptor. Attach them both to the stove using 8 of the screws provided.
- 4) Install the elbow section with gasket ring so that the inner pipe slides over the 4" inner portion of the stove adaptor previously installed. Screw 6 of the remaining screws through the back of the elbow and into the stove. The last 2 screws are used to secure the top lip of the elbow to the top of the stove.

To complete the installation follow the instructions provided by Dura-Vent. Ensure all stove and termination clearances outlined in the Owner's Manual are properly observed.