



# Technical Data Sheet

## Sterling-HT DV 8532 5" X 8" Rear Exit Starter Kit Install *Kit 95-61223HA*

**Publish Date: 6/4/2001**

### **KIT CONTENTS:**

- (16)#4500-3435 - Screws 8-32 X 3/8" Type F PH
- (1)#3160-101 - 5" X 6-1/2" Gasket Ring
- (1)#3160-102 - 8" X 9-1/2" Gasket Ring
- (1)#5701-1223HA - 5" X 8" Horizontal Stove Adaptor (Twist Lock)

### **TOOLS REQUIRED:**

Phillips Screwdriver

### **PROCEDURE:**

- 1) Locate and remove the temporary shipping screws from the inner collar mounting holes with a Phillips screwdriver.
- 2) Place the 5" X 6-1/2" gasket ring onto the end of the inner (5") portion of the stove adaptor. Attach them to the stove with 8 of the screws provided.

**HINT:** Use Spray 'n Glue or liquid gasket glue to help hold the gasket rings in place during assembly.

- 3) Place the 8" X 9-1/2" gasket ring onto the end of the outer (8") portion of the stove adaptor. Attach them to the stove using the remaining 8 screws.

Follow the installation instructions provided by Dura-Vent to complete the installation. Ensure all stove and termination clearances outlined in the Owner's Manual are observed.