



Green Mountain 80

 Model 8681 · Available Spring 2025

With a new silhouette and refined details, the GM80 is at home in both contemporary and traditional homes alike. Along with its stylish new appearance, the GM80 model 8681 continues to deliver high efficiency and exceptional heating performance, thanks to our TruHybrid™ combustion system.




New Product Highlights

FLUSH DOOR

· CAST TEXTURE

· 6 INCH FLUE

The Green Mountain 80 has a traditional black finish that highlights the clean modern style of the cast iron. Soapstone lining adds the HearthStone HeatLife™, retaining heat and radiating warmth for hours to keep your home cozy.





Green Mountain 80

NEW Model 8681 · Available Spring 2025

Style

The GM80 starts a new generation of the Green Mountain Family. The new style is defined by an elegant silhouette, linear cast iron texture, and flush door supported by hidden hinges.

Handles

A new handle design uses our roller latch to give a secure and satisfying click, so you can feel confident that the door is fully closed and locked in place.

Ø 6 in. Flue

The GM80 8681 features a more versatile 6" flue. To support the 3.1 cu.ft. firebox, we focused on the ease of airflow through the stove. The result is large stove that is easy to start and efficient to burn.

Rear Exit

We incorporated the optional rear exit to provide more installation scenarios.



Specifications

Combustion Technology	TruHybrid™
HHV Efficiency	80%
HeatLife™*	Up to 30 hours
EPA Certified	0.53 g/hr
Heats up to	2,500 sq ft
Firebox Capacity	3.16 cu ft
BTU	Up to 80,000
Maximum Log Length	23"
Flue Exit & Diameter	Top or Rear - 6"
Weight	550 lbs
Dimensions W x D x H	29½" x 25" x 31"

Accessories

Rear Heat Shield	5968-011
Blower Kit	96-57801
Outside Air Adapter	96-53400

Finish Options

Matte Black	
-------------	--

Hearth Pad: Ember Only

USA - Width x Depth	41½" x 40"
Canada - Width x Depth	45" x 50"

Clearances

Single-wall connector pipe, no rear heat shield	
Side / Rear / Corner	17.5" / 15.5" / 7.5"
Single-wall connector pipe with rear heat shield	
Side / Rear / Corner	17.5" / 5.5"+ / 7.5" USA 17.5" / 15.5" / 7.5" CAN
Double-wall connector pipe with rear heat shield	
Side / Rear / Corner	17.5" / 3.5" / 7.5"

* Under the right conditions, you will be able to start a new fire with kindling up to the end of the product's HeatLife™.
* Single-wall connector pipe generally requires 18 inches of clearance.

Note: All information is for reference only. Refer to the owner's manual for full specification and installation details.

www.hearthstonestoves.com

